

CIRRUS SPECIFICATION SHEET

PHYSICAL PROPERTIES

	U.S. Units	Metric Units
Total Weight:	20 oz per linear yd	620.06g per linear meter
Fabric Weight:	2.7 oz per linear yd	83.71g per linear meter
Vinyl Weight:	16.8 oz per linear yd	520.86g per linear meter
Thickness:	0.017 in	0.43 mm
Fabric:	Highly reflective surface. Backing is poly-cotton woven or polyester/ pulp non-woven depending on face emboss.	

PRODUCT PACKAGING

Roll Size:	54", 60", 75"
Core Diameter:	3 inch ID Heavy Duty

SPECIFICATIONS TESTING CERTIFICATION

Federal Specification:	CCC-408-D Type II
WA Speciafication:	W-101 Type II

FIRE TESTING

NFPA Life Safety Code 101:	Class A
ASTM-E84 Tunnel Test:	Class A
CAN/ULC-S102.2:	Passed all requirements
NFPA 286 Corner Burn Test:	Class A
BS476 Parts 6 & 7:	Passed all requirements
EU Class Flame (EN 15102):	Passed Class B, s2
ASTM-G21 Specification:	Passed all requirements

Made with Low VOC vinyl
Tested per CA-1350 Air Quality Standards Cadmuim & Lead Free Formulation
Meets or exceeds requirements for Flame Spread, Smoke Developed, & Flashover